

Groeneveld-BEKA GP

Modular and flexible, suitable for every need



Groeneveld-BEKA GP

The Groeneveld-BEKA GP series is a new developed modular progressive lubrication system, combining a single pump concept with different reservoir types and sizes. The GP series is designed for progressive lubrication on mobile applications like tippers, mobile cranes, garbage trucks, compact construction equipment, agricultural machines, telehandlers and reachstackers. The pump is easy to adjust and adaptable to the lubrication needs of the machine.

The GP series has been designed for easy service and exchange of sealed for life components. Adjusting the system to the lubrication needs and thus upgrading the system, as well as servicing the system, will be easy due to the modular concept of the GP.

- Interchangeable components make it easy to service and adjust
- Easy maintenance
- OEM quality standards, compliant with IATF & SPICE regulations
- Suitable for greases up to NLGI-2, including biodegradable greases

Modular system

The GP series consists of 3 interchangeable modules, a top, central and lower module. All modules are easy to maintain, replace or upgrade.

Top module: the reservoir

The GP series is available with 3 different kind of reservoirs and different volumes. All reservoirs are interchangeable and can easily be placed on the central module.

Central module: the drive unit

The GP series comes with 2 different drive units, a 12V and a 24V version.

Grease outlets

The GP series has a maximum of 3 grease outlets with each a separate piston with direct delivery to the main line. Two outlets are plugged as a standard.

The standard piston has an output of 2.5 cc/min. Optionally a larger piston with an adjustable output from 2 up to 4 cc/min can be installed. The pistons are easily exchangeable.

The option for 3 different outlets makes it easier to lubricate different greasing points on complex machinery.

Lower module

The lower module is available in two options, the GPA and the GPA+. The GPA is delivered without a control unit as a standard.

The co-molded gasket and self-holding screws in the bottom cover make the GP series easy to assemble and service without the risk of parts getting lost.



Reservoir types

There are 3 different kind of interchangeable reservoir types to adjust the system to the lubrication needs of the machine.



Paddle reservoir

The paddle reservoir is installed on the GP series as a standard and is equipped with a paddle blade. The rotation of the paddle blade minimizes air pockets and grease separation in the reservoir and dispense the grease to the pistons.

The paddle reservoir is available in 2.5, 5 and 8 liter.



Follower plate reservoir

When in need of reservoir with a follower plate, the standard paddle blade reservoir can be replaced. The follower plate reservoir makes it possible to use the GP series on static and rotating applications.

The follower plate helps compress the grease as it is used to prevent air pockets forming, ageing of the grease as well as oxidation from air or water. This also makes the follower plate reservoir suitable to use with biodegradable greases.

Another advantage of the follower plate is that all the grease in the reservoir is used and the reservoir wall remains clean, allowing you to check the grease level visually.

The follower plate reservoir is available in 3, 5 and 8 liter.



Cartridge reservoir

The cartridge version reservoir is equipped with a unique 3 liter grease cartridge. This capacity meets the lubrication needs and service interval of most modern compact to mid-size machines.

The grease cartridge makes exchanging of the grease cartridge easy and ensures that the correct grease is used. Since the grease is in a cartridge it is protected from ageing as well as oxidation from air or water, which also makes this system extremely suitable to use with biodegradable greases.

The cartridge is delivered with NLGI-2 grease as a standard, but can be filled with other greases on request.

Lower module

The GP series is delivered with the GPA lower module, without an integrated control unit. The lower module can easily be upgraded to the GPA+ lower module, which offers an integrated control unit.

The GPA+ lower unit has an integrated control unit with a 4 digit display and touch pads making it easy to program, adjust the greasing interval and grease output, and check the system status. Alarms and warning messages are also showed on the display.



GPA lower module



GPA+ lower module

Working principle



The GP system consists of a pump with grease reservoir and up to 3 internal grease pistons. Two pistons are plugged as a standard. Optionally the system can be controlled with a single block switch.

When the pump is activated, grease is pumped through the pump elements. The pistons transfer the grease to the progressive distributors. The progressive distributors supply the exact amount of grease to each of the lubrication points.

Technical information

Pump type	Electric piston progressive pump
Reservoir types and volumes	Standard: Paddle version, 2.5, 5 or 8 liter Optional: Follower version, 3, 5 or 8 liter Optional: Cartridge version, 3 liter
No. of outputs	Max. of 3 outlets, 2 plugged as a standard
Piston	Standard: 2 cc/min ø6 Optional: 2-4 cc/min ø8 adjustable outlet
Relieve valve	Internal
Maximum operating pressure	250 bar (3625 psi)
Grease class	Grease up to NLGI-2 Biodegradable greases only to be used in follower plate or cartridge reservoir
Temperature range	-20 up to +70 °C (-4 up to 158 °F)
Supply voltage	12 or 24 Vdc
Protection class	IP54 (reservoir) IP69K (electronic compartment)
Regulations / EMC	ECE-R10, rev. 6 Automotive directive of the United Nations ISO 13766: 2006 Earth Moving Machinery standard ISO14982: 2009 Agriculture and Forestry Machinery standard EN 12895: 2015 Industrial Truck standard EN 13309: 2010 Construction Machinery standard EN 50498: 2010 After Market Electronic Equipment in vehicles UL 778:2016 Certification

www.plantcare.com.cn

普朗科（北京）科技有限公司
Plantcare (Beijing) Co.,Ltd



Add :北京市朝阳区高碑店乡西店村15号楼15号面江湖二层
Tel :+86 10 85777020
Phone :+86 18611525353
Email :wuhm@plantcare.com.cn